



USES® SHUNT EFFICIENCY SYSTEMS
AMPERAGE MEASURED ON CONDUCTORS
FROM USES® UNIT WITH UNIT ENERGIZED

USES® UNIT	L1	L2	L3	NEUTRAL
RDES-1	3.7	3.7	-----	-----
CMES-1	10.0	10.0	-----	0.1
CMES-3Y	11.0	11.0	11.0	0.1
CMES-3D	20.0	20.0	20.0	-----
CMES-3Y(480)	17.6	17.5	17.2	0.1
CMES-3D(480)	24.8	24.6	24.8	-----
CMES-3Y(600)	24.0	24.0	24.0	-----
CMES-3D(600)	32.1	32.1	32.3	-----
CMES-3Y-H	10.0	11.0	10.0	0.1
CABO-120	4.5	-----	-----	4.5
CABO-240	3.7	3.7	-----	-----
BL-120	1.0	-----	-----	1.0
BL-208/240	3.0	3.0	-----	-----
BL-300	2.0	-----	-----	2.0
BLM-3Y(208)	6.0	6.0	6.0	0.1
BLM-3D(208)	9.2	9.2	9.2	-----
BLM-3Y(480)	6.2	6.3	6.4	0.1
BLM-3D(480)	9.7	9.9	9.9	-----

NOTE: AMPERAGE READINGS ARE APPROXIMATE. THERE MAY BE A 20% VARIANCE FROM THESE FIGURES.

©1996 USES MFG INC. All Rights Reserved

USES MFG INC. PO Box 156, 152 Old Colchester Road, Quaker Hill, Connecticut, USA 06375 • Telephone (860) 443-8737 Fax (860) 439-1515